
USING THE STANDARD TEMPLATE LIBRARY (STL)

Lars Ole Schwen

MEVIS Developer Seminar, 2015-09-02

```
#include<algorithm>
#include<vector>

int main ( const int, const char** const ) {
    const unsigned short myArray[5] = { 4, 7, 1, 1, 42 };
    std::vector<unsigned short> myVec ( myArray, myArray+5 );
    std::shuffle ( myVec.begin(), myVec.end(), std::mt19937 ( 23 ) );
    std::vector<unsigned short>::const_iterator
        it = std::find ( myVec.begin(), myVec.end(), 42 );
    return ( EXIT_SUCCESS );
}
```

USING THE STANDARD TEMPLATE LIBRARY (STL)

1. Introduction
2. Concepts
3. Containers
4. Iterators
5. Algorithms and Utilities

1. Introduction

Contents

1. Introduction

2. Concepts

3. Containers

4. Iterators

5. Algorithms and Utilities

1. Introduction

Disclaimer

This talk is about ...

- concepts of STL
- examples of STL usage
- examples should work with C++-11
(compiled on gcc-4.6.3, clang 3.6, and
Visual Studio 2013)
- code examples available
(incomplete excerpts in slides)
- Thanks to Hans M. for feedback!

1. Introduction

Disclaimer

This talk is about ...

- concepts of STL
- examples of STL usage
- examples should work with C++-11
(compiled on gcc-4.6.3, clang 3.6, and Visual Studio 2013)
- code examples available
(incomplete excerpts in slides)
- Thanks to Hans M. for feedback!

... but

- I'm not a native STL speaker
- not exhaustive about STL
- no reference, see
<http://www.cplusplus.com/reference>
instead
- some observations may not be guaranteed
- boost or other libraries may offer better solutions for your needs
- example code quality not optimal
- not covered:
 - STL smart pointers
 - multithreading
 - exception handling
 - strings, stringstream

1. Introduction

Further Reading


The screenshot shows a Mozilla Firefox browser window with the following details:

- Title Bar:** Reference - C++ Reference - Mozilla Firefox
- Address Bar:** http://www.cplusplus.com/reference/
- Toolbar:** Standard browser toolbar with icons for back, forward, search, and refresh.
- Header:** Search bar and "Not logged in" status with "register" and "log in" buttons.
- Left Sidebar:** A sidebar titled "C++" containing links to Information, Tutorials, Reference, Articles, and Forum. The "Reference" link is currently selected.
- Content Area:**
 - Section:** Reference
 - Section:** Standard C++ Library reference
 - Section:** C Library
 - Description:** The elements of the C language library are also included as a subset of the C++ Standard library. These cover many aspects, from general utility functions and macros to input/output functions and dynamic memory management functions:
 - Table:** A list of C library headers with their descriptions.

<code><cassert> (cassert.h)</code>	C Diagnostics Library (header)
<code><cctype> (ctype.h)</code>	Character handling functions (header)
<code><cerrno> (errno.h)</code>	C Errors (header)
<code><cfenv> (fenv.h)</code>	Floating-point environment (header)
<code><cfloat> (float.h)</code>	Characteristics of floating-point types (header)

1. Introduction

Further Reading



2. Concepts

Contents

1. Introduction

2. Concepts

3. Containers

4. Iterators

5. Algorithms and Utilities

2. Concepts

STL

- templates extensively used (with all pros and cons)

2. Concepts

STL

- templates extensively used (with all pros and cons)
- lowercase_names_with_underscores

2. Concepts

STL

- templates extensively used (with all pros and cons)
- lowercase_names_with_underscores
- data structures (containers) for specific use cases

2. Concepts

STL

- templates extensively used (with all pros and cons)
- lowercase_names_with_underscores
- data structures (containers) for specific use cases
- generic access by iterators

2. Concepts

STL

- templates extensively used (with all pros and cons)
- lowercase_names_with_underscores
- data structures (containers) for specific use cases
- generic access by iterators
- algorithms and utilities **independent of containers**

2. Concepts

STL

- templates extensively used (with all pros and cons)
- lowercase_names_with_underscores
- data structures (containers) for specific use cases
- generic access by iterators
- algorithms and utilities **independent of containers**
- efficient (memory, time) if used correctly

2. Concepts

STL

- templates extensively used (with all pros and cons)
- lowercase_names_with_underscores
- data structures (containers) for specific use cases
- generic access by iterators
- algorithms and utilities **independent of containers**
- efficient (memory, time) if used correctly
- complexity guarantees

2. Concepts

First Example

```
#include<cstdlib>
#include<vector>

int main ( const int, const char** const ) {
    const unsigned int size = 10;
    std::vector<unsigned int> myVec(size);
    for ( unsigned int i = 0; i < size; ++i ) {
        myVec[i] = 42*i+23;
    }
    return ( EXIT_SUCCESS );
}
```

~~~ STLSimple.cpp

✗ not very STLish

### **3. Containers**

#### **Contents**

1. Introduction

2. Concepts

**3. Containers**

4. Iterators

5. Algorithms and Utilities

### 3. Containers

#### Selected Containers

- **std::vector**

- one-dimensional array
- random access via index

### 3. Containers

#### Selected Containers

- **std::vector**
  - one-dimensional array
  - random access via index
- **std::list**
  - bidirectionally linked list
  - cheap insertion
  - extension: **std::forward\_list**

### 3. Containers

#### Selected Containers

- **std::vector**
  - one-dimensional array
  - random access via index
- **std::list**
  - bidirectionally linked list
  - cheap insertion
  - extension: `std::forward_list`
- **std::set**
  - mathematical set: objects contained once
  - internally sorted
  - extensions: `std::multiset`, `std::unordered_set`

### 3. Containers

#### Selected Containers

- **std::vector**
  - one-dimensional array
  - random access via index
- **std::list**
  - bidirectionally linked list
  - cheap insertion
  - extension: `std::forward_list`
- **std::set**
  - mathematical set: objects contained once
  - internally sorted
  - extensions: `std::multiset`, `std::unordered_set`
- **std::map**
  - “dictionary”, values for unique keys
  - internally sorted
  - extensions: `std::multimap`, `std::unordered_map`

### 3. Containers

#### Vectors

`std::vector<DataType>`

- one-dimensional array with dynamic size
- random access via index
- special `std::vector<bool>`

### 3. Containers

#### Vector 1

```
#include<vector>
// ...
std::vector<unsigned int> myVec(size); // create, 0-initialized

myVec[5] = 42; // random access
myVec.at(3) = 23; // random access with bounds checking

myVec.resize(12); // change size

myVec.push_back(23); // insert at (change size)
myVec.pop_back(); // remove last element

myVec.reserve(120); // allocation is logarithmic, but still ...

// iterate, note the "auto" keyword (C++ 11)
for ( auto it = myVec.begin(); it != myVec.end(); ++it ) {
    std::cout << *it << std::endl;
}

myVec.clear(); // resize to 0
```

↔ STLVector\_Basic.cpp

### 3. Containers

#### Vector 2

```
#include<vector>
#include<algorithm>
// ...
std::vector<signed int> myVecA, myVecB;
// ... // fill vectors

// insert via iterator
std::vector<signed int>::iterator destPos = myVecA.begin();
++destPos; ++destPos;
myVecA.insert ( destPos, myVecB.rbegin(), myVecB.rend() );

// delete values (not indices) 60 (included) ... 275 (excluded!)
signed int
    firstEntryToDelete = 60,
    firstEntryAfterDeletion = 275;
std::vector<signed int>::iterator
    rangeBegin = std::find ( myVecA.begin(), myVecA.end(), firstEntryToDelete ),
    rangeEnd = std::find ( myVecA.begin(), myVecA.end(), firstEntryAfterDeletion );
myVecA.erase ( rangeBegin, rangeEnd );
```

↔ [STLVector\\_Advanced.cpp](#)

### 3. Containers

#### Lists

`std::list<DataType>`

- bidirectionally linked list
- no random access
- cheap insertion
- extension: `std::forward_list`

### 3. Containers

#### List 1

```
#include<list>

std::list<unsigned int> myList; // no size

for ( int i = 0; i < 12; ++i ) {
    myList.push_back ( 4 * i + 3 );
}

std::cout << "myList is of size " << myList.size() << std::endl;
// iterate over list
for ( auto it = myList.begin(); it != myList.end(); ++it ) {
    std::cout << *it << std::endl;
}
```

### 3. Containers

#### List 2

```
std::list<unsigned int>::iterator it = myList.begin();
++it; ++it;
myList.insert ( it, 21859275 ); // insert new entry before it
                                // this is cheaper than for vectors
--it;
myList.erase ( it );

myList.push_front ( 4711 );
myList.push_back ( 28359 );

myList.pop_back();
myList.pop_front();

myList.clear(); // resize to 0
```

↔ STLList\_Basic.cpp

### 3. Containers

#### List 3

```
#include<list>

struct isOdd {
    template<typename IntegerType>
    bool operator() ( const IntegerType &Value ) {
        return ( ( Value % 2 ) == 1 );
    }
};

// in main program:
std::list<signed long int> myListA, myListB;

std::list<signed long int>::iterator myIt = myListA.begin();
std::advance ( myIt, 3 );
myListA.splice ( myIt, myListB );

myListA.sort();           // List-specific variants of generic
myListA.remove ( 65 );   // sort, remove, unique, remove_if
myListA.unique();
myListA.remove_if ( isOdd() );
```

» STLList\_Advanced.cpp

### 3. Containers

#### Vector vs. List 1

When using objects that are expensive to handle ...

```
struct ExpensiveToCreate {
    ExpensiveToCreate ( ) : _val ( 0 ) {
        std::cout << "EXPENSIVE create" << std::endl;
    }
    ExpensiveToCreate ( const size_t Val ) : _val ( Val ) {
        std::cout << "EXPENSIVE create" << std::endl;
    }
    // ...
    // similar for destructor, copy constructor, operator=
    bool operator< ( const ExpensiveToCreate& Other ) const {
        return ( ( this->_val < Other._val ) );
    }

private:
    size_t _val;
};
```

### 3. Containers

#### Vector vs. List 2

... choose an efficient data structure!

```
const size_t mySize = 4;

std::vector<ExpensiveToCreate> myVector ( mySize );
for ( size_t i = 0; i < mySize; ++i ) {
    myVector[i] = ExpensiveToCreate ( mySize - i );
}
std::sort ( myVector.begin(), myVector.end() );

std::list<ExpensiveToCreate> myList;
for ( size_t i = 0; i < mySize; ++i ) {
    myList.emplace_back ( i );
}
myList.sort();
```

↔ STLVectorVsList.cpp

### 3. Containers

#### Benchmark: List vs. Forward List

```
std::list<signed long int> myListC;
fillWithSomeData ( myListC );
std::cout << "Modifying list..." << std::flush;
std::chrono::high_resolution_clock::time_point
    t1 = std::chrono::high_resolution_clock::now();

for ( size_t i = 0; i < ListSize; ++i ) {
    typename std::list<signed long int>::iterator it = myListC.begin();
    ++it;
    myListC.insert ( it, 4711 );
}

std::chrono::high_resolution_clock::time_point
    t2 = std::chrono::high_resolution_clock::now();
const std::chrono::duration<double>
    timeSpan = std::chrono::duration_cast<std::chrono::duration<double>>(t2 - t1);
std::cout << "done, took" << timeSpan.count() << std::endl;
```

### 3. Containers

#### Benchmark: List vs. Forward List

```
std::forward_list<signed long int> myListD;
fillWithSomeData ( myListD );
std::cout << "Modifying forward list..." << std::flush;
std::chrono::high_resolution_clock::time_point
    t1 = std::chrono::high_resolution_clock::now();

for ( size_t i = 0; i < ListSize; ++i ) {
    typename std::forward_list<signed long int>::iterator it = myListD.begin();
    ++it;
    myListD.insert_after ( it, 4711 );
}

std::chrono::high_resolution_clock::time_point
    t2 = std::chrono::high_resolution_clock::now();
const std::chrono::duration<double>
    timeSpan = std::chrono::duration_cast<std::chrono::duration<double>>(t2 - t1);
std::cout << "done, took" << timeSpan.count() << std::endl;
```

↔ STLForwardList.cpp

### 3. Containers

#### A Note on Code Optimization

Avoid premature optimization (runtime, memory).

### 3. Containers

#### A Note on Code Optimization

Avoid premature optimization (runtime, memory). Instead,

1. make it **work**
2. make it **reproducible**
3. **quantify performance** by profiling
4. make it **fast**

### 3. Containers

#### A Note on Code Optimization

Avoid premature optimization (runtime, memory). Instead,

##### 1. make it **work**

- write a simple implementation of what you want
- don't try to be clever (but don't be stupid, either)

##### 2. make it **reproducible**

##### 3. **quantify performance** by profiling

##### 4. make it **fast**

### 3. Containers

#### A Note on Code Optimization

Avoid premature optimization (runtime, memory). Instead,

##### 1. make it **work**

- write a simple implementation of what you want
- don't try to be clever (but don't be stupid, either)

##### 2. make it **reproducible**

- make sure you have appropriate regression tests
- this will simplify later optimization

##### 3. **quantify performance** by profiling

##### 4. make it **fast**

### 3. Containers

#### A Note on Code Optimization

Avoid premature optimization (runtime, memory). Instead,

##### 1. make it **work**

- write a simple implementation of what you want
- don't try to be clever (but don't be stupid, either)

##### 2. make it **reproducible**

- make sure you have appropriate regression tests
- this will simplify later optimization

##### 3. **quantify performance** by profiling

- consider typical use cases (and document them)
- be surprised where time is spent (and where compilers have already done a good job)

##### 4. make it **fast**

### 3. Containers

#### A Note on Code Optimization

Avoid premature optimization (runtime, memory). Instead,

##### 1. make it **work**

- write a simple implementation of what you want
- don't try to be clever (but don't be stupid, either)

##### 2. make it **reproducible**

- make sure you have appropriate regression tests
- this will simplify later optimization

##### 3. **quantify performance** by profiling

- consider typical use cases (and document them)
- be surprised where time is spent (and where compilers have already done a good job)

##### 4. make it **fast**

- optimize implementation where needed
- use regression tests to avoid breaking it

### 3. Containers

#### A Note on Code Optimization

Avoid premature optimization (runtime, memory). Instead,

##### 1. make it **work**

- write a simple implementation of what you want
- don't try to be clever (but don't be stupid, either)

##### 2. make it **reproducible**

- make sure you have appropriate regression tests
- this will simplify later optimization

##### 3. **quantify performance** by profiling

- consider typical use cases (and document them)
- be surprised where time is spent (and where compilers have already done a good job)

##### 4. make it **fast**

- optimize implementation where needed
- use regression tests to avoid breaking it

*"More computing sins are committed in the name of efficiency (without necessarily achieving it) than for any other single reason—including blind stupidity." (William Wulf)*

### 3. Containers

#### Sets

`std::set<DataType>`

- mathematical set: objects contained once
- internally sorted according to comparison
- no direct (write) access
- fast find
- extensions
  - `std::multiset<DataType>` can contain multiple instances
  - `std::unordered_set<DataType>` hashed, not sorted

### 3. Containers

#### Set 1

```
#include<set>
// ...
std::set<short int> mySet;
for ( int i = 0; i < 25; ++i ) {
    const short int val = ( 12 * i + 2 ) % 26;
    mySet.insert ( val );
}
std::cout << "mySet is of size" << mySet.size() << std::endl;
// note: no random access

std::cout << "\Removed" << mySet.erase ( 12 ) << "\times entry 12." << std::endl
      << "\Removed" << mySet.erase ( 13 ) << "\times entry 13." << std::endl;
```

### 3. Containers

#### Set 2

```
// iterate over set, as before
for ( auto it = mySet.begin(); it != mySet.end(); ++it ) {
    std::cout << *it << std::endl;
}

std::set<short int>::iterator pos = mySet.find( 16 );
std::cout << "16 found:" << *pos << std::endl;

std::set<short int>::iterator otherPos = mySet.find( 23 );
if ( otherPos == mySet.end() ) {
    std::cout << "the following results in undefined behavior" << std::endl;
    std::cout << "23 not found:" << *otherPos << std::endl; // dereferencing undefined!
}
```

⇒ [STLSet\\_Basic.cpp](#)

### 3. Containers

#### Unordered Set and Multiset 1

```
template<typename SetType>
void fillAndPrint ( ) {
    SetType mySet;

    for ( int i = 0; i < 25; ++i ) {
        const short int val = ( 12 * i + 2 ) % 26;
        std::cout << "inserting" << val << std::endl;
        mySet.insert ( val );
    }

    std::cout << "mySet is of size" << mySet.size() << std::endl;

    for ( auto it = mySet.begin(); it != mySet.end(); ++it ) {
        std::cout << *it << std::endl;
    }
    std::cout << std::endl;
}
```

### 3. Containers

#### Unordered Set and Multiset 2

```
#include<set>
#include<unordered_set>
// ...
std::cout << "Multiset:" << std::endl;
fillAndPrint < std::multiset<short int> > ();

std::cout << "Unordered_Set:" << std::endl;
fillAndPrint < std::unordered_set<short int> > ();

std::cout << "Unordered_Multiset:" << std::endl;
fillAndPrint < std::unordered_multiset<short int> > ();
```

### 3. Containers

#### Unordered Set: More about Hashing

```
#include<set>
#include<unordered_set>
// ...

std::unordered_set<std::string> myUnorderedSet;

for ( int i = 0; i < 25; ++i ) {
    std::string number = "Number" + std::to_string ( i );
    std::cout << "inserting" << number << " with hash"
        << myUnorderedSet.hash_function() ( number ) << std::endl;
    myUnorderedSet.insert ( number );
}

std::cout << "Load factor is" << myUnorderedSet.load_factor()
    << ", there are" << myUnorderedSet.bucket_count() << " buckets." << std::endl;

std::string num23 ( "Number23" );
std::cout << num23 << " is in bucket" << myUnorderedSet.bucket ( num23 ) << std::endl;
```

≈ STLSet\_Extensions.cpp

### 3. Containers

#### Maps

`std::map<KeyType, ValueType>`

- “dictionary”, values for unique keys
- internally sorted according to comparison
- fast lookup
- access via `operator[]` somewhat tricky
- extensions
  - `std::multimap<KeyType, ValueType>` can contain multiple value per key
  - `std::unordered_map<KeyType, ValueType>` hashed, not sorted

### 3. Containers

#### Map 1

```
#include<map>
#include<string>
// ...
std::map<short int, std::string> myMap;
myMap[1] = "One"; // inserting elements works via operator[]
myMap.insert ( std::pair<short int, std::string> ( 2, "Two" ) );
myMap.insert ( std::make_pair ( 3, "Three" ) );

std::cout << "1:" << myMap[1] << std::endl; // access also works via operator[]

std::cout << "4:" << myMap[4] << std::endl;
                    // there is no const access, default object created instead!

auto it = myMap.find ( 1 );
std::cout << it->first << ":" << it->second << std::endl; // iterator points to pair

it = myMap.find ( 5 );
std::cout << ( it == myMap.end() ) << std::endl;
```

### 3. Containers

#### Map 2

```
#include<map>
#include<string>
// ...
std::map< std::string, short int>
    myOtherMap = { { "Zero", 0 },
                  { "One", 1 },
// ...
                  { "Eight", 8 },
                  { "Nine", 9 } };
// alternative form of initialization

// this is how one can iterate over a map
for ( auto it = myOtherMap.begin(); it != myOtherMap.end(); ++it ) {
    std::cout << it->first << " " << it->second << std::endl;
} // note: the map is sorted
```

⇒ [STLMap\\_Basic.cpp](#)

### 3. Containers

#### Map 3

```
#include<map>
#include<string>
// ...
std::map<short int, std::string> myMap;
myMap[1] = "One"; // inserting elements works via operator[]
myMap[2] = "Two";
std::string dwarf = myMap[3];

// access including existence check and const access via at()
for ( short int i = 0; i < 5; ++i ) {
    std::string myString;
    try {
        myString = myMap.at ( i );
    } catch ( std::exception &ex ) {
        std::cout << "exception caught:" << ex.what() << std::endl;
        myString = "not found";
    }
    std::cout << i << ":" << myString << std::endl;
}
```

### 3. Containers

#### Unordered Map

```
#include<unordered_map>
#include<string>
// ...
std::unordered_map< std::string, short int>
myOtherMap = { { "Zero", 0 },
               { "One", 1 },
               { "Two", 2 },
               { "Three", 3 },
               { "Four", 4 },
               { "Five", 5 },
               { "Six", 6 },
               { "Seven", 7 },
               { "Eight", 8 },
               { "Nine", 9 } };
// alternative form of initialization

// iteration as usual (for maps)
for ( auto it = myOtherMap.begin(); it != myOtherMap.end(); ++it ) {
    std::cout << it->first << ":" << it->second << std::endl;
}
```

### 3. Containers

#### Multimap 1

```
#include<map>
#include<string>
// ...
std::multimap<unsigned int, std::string>
    myMap = { { 1, "one" },
              { 1, "eins" },
// ...
              { 3, "three" },
              { 3, "drei" } };
// no access via operator[]
for ( auto it = myMap.begin(); it != myMap.end(); ++it ) {
    std::cout << it->first << " " << it->second << std::endl;
}
```

### 3. Containers

#### Multimap 2

```
std::cout << "number of occurrences of 1 and 4:"  
    << myMap.count ( 1 ) << " " << myMap.count ( 4 ) << std::endl;  
  
// here's how to iterate over values with the same key  
typedef std::multimap<unsigned int, std::string>::const_iterator citType;  
std::pair< citType, citType >  
    range = myMap.equal_range ( 2 );  
for ( citType it = range.first; it != range.second; ++it ) {  
    std::cout << it->first << " " << it->second << std::endl;  
}
```

↔ [STLMap\\_Advanced.cpp](#)

### 3. Containers

#### Caution: Set and Map with Floating Point Numbers

```
const double
oneThirdA = 1.0/3.0f,
oneThirdB = A::getOneOverThirty() / 2 + 9.5f * A::getOneOverThirty(),
oneThirdC = 10.0f * A::getOneOverThirty();

std::map<double, std::string> myMap;
myMap [ oneThirdA ] = "one\u00fcthird\u00d7A";
myMap [ oneThirdB ] = "one\u00fcthird\u00d7B";

std::cout << "should\u00d7be\u00d7oneThird\u00d7A\u00d7or\u00d7B:\u00d7"
      << myMap [ 10.0f * A::getOneOverThirty() ] << std::endl;

myMap [ oneThirdC ] = "one\u00fcthird\u00d7C";

for ( auto it = myMap.begin(); it != myMap.end(); ++it ) {
    std::cout << it->first << "\u00d7" << it->second << "\u00d7";
    printAsHex ( it->first );
    std::cout << std::endl;
}
```

↔ STLMAP\_HowNotTo.cpp

## **4. Iterators**

### **Contents**

1. Introduction

2. Concepts

3. Containers

**4. Iterators**

5. Algorithms and Utilities

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator
- unidirectional vs. bidirectional vs. random access iterators

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator
- unidirectional vs. bidirectional vs. random access iterators
  - `++it, --it, itA < itB,`

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator
- unidirectional vs. bidirectional vs. random access iterators
  - `++it, --it, itA < itB,`
- reverse\_iterator vs. iterator

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator
- unidirectional vs. bidirectional vs. random access iterators
  - `++it, --it, itA < itB,`
- **reverse\_iterator** vs. **iterator**
  - `for ( std::vector<...>::reverse_iterator it = vec.rbegin(); it != myVec.rend(); ++it )`

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator
- unidirectional vs. bidirectional vs. random access iterators
  - `++it, --it, itA < itB,`
- **reverse\_iterator** vs. **iterator**
  - `for ( std::vector<...>::reverse_iterator it = vec.rbegin(); it != myVec.rend(); ++it )`
- **const\_iterator** vs. **iterator**

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator
- unidirectional vs. bidirectional vs. random access iterators
  - `++it, --it, itA < itB,`
- **reverse\_iterator** vs. **iterator**
  - `for ( std::vector<...>::reverse_iterator it = vec.rbegin(); it != myVec.rend(); ++it )`
- **const\_iterator** vs. **iterator**
  - prevent modifying container contents

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator
- unidirectional vs. bidirectional vs. random access iterators
  - `++it, --it, itA < itB,`
- **reverse\_iterator** vs. **iterator**
  - `for ( std::vector<...>::reverse_iterator it = vec.rbegin(); it != myVec.rend(); ++it )`
- **const\_iterator** vs. **iterator**
  - prevent modifying container contents
  - **const\_iterators** can still be incremented

## 4. Iterators

### Iterators

- iterators can be used similarly for different containers
- replacable by pointers (see sorting example later) or anything that behaves like an iterator
- unidirectional vs. bidirectional vs. random access iterators
  - `++it, --it, itA < itB,`
- **reverse\_iterator** vs. **iterator**
  - `for ( std::vector<...>::reverse_iterator it = vec.rbegin(); it != myVec.rend(); ++it )`
- **const\_iterator** vs. **iterator**
  - prevent modifying container contents
  - **const\_iterators** can still be incremented
- iterators (pointers, references) may survive container modification or not

## 5. Algorithms and Utilities

### Contents

1. Introduction

2. Concepts

3. Containers

4. Iterators

5. Algorithms and Utilities

## 5. Algorithms and Utilities

### Debugging Support

compiler define `_GLIBCXX_DEBUG`:

```
g++ -std=c++0x -g -D_GLIBCXX_DEBUG  
-lm -o STLDebugging.bin_d STLDebugging.cpp
```

```
#include<cstdlib>  
#include<iostream>  
#include<vector>  
  
int main ( const int, const char** const ) {  
    const unsigned int size = 2;  
    std::vector<unsigned int> myVec(size);  
    myVec.clear();  
    myVec[1] = 42;  
    // myVec.at(1) = 42;  
    return ( EXIT_SUCCESS );  
}
```

↔ STLDebugging.cpp

## 5. Algorithms and Utilities

### Predicates

- functions returning Boolean value
- always return same value (no internal state)
- e.g., comparison for sorting

```
bool isDivisibleByFour ( const int &Arg ) {  
    return ( ( Arg % 4 ) == 0 );  
}
```

## 5. Algorithms and Utilities

### Functors (Function Objects)

- object with `operator()`
- behave like a function, but more general

```
class UniqueNumberGenerator {  
public:  
    UniqueNumberGenerator() : _num ( 0 ) {  
    }  
  
    int operator()() {  
        _num += 3;  
        return ( _num );  
    }  
  
private:  
    int _num;  
};
```

## 5. Algorithms and Utilities

### Algorithms

- some examples of container methods seen above
- STL offers **generic** algorithms independent of STL data structures
- access via iterators or iterator-likes

## 5. Algorithms and Utilities

### Pairs

```
#include<list>
#include<limits>

template<typename T>
std::pair<T, unsigned int> findMaximumAndItsPosition ( std::list<T> &Arg ) {
    std::pair<T, unsigned int> res ( - std::numeric_limits<T>::infinity(),
                                    std::numeric_limits<unsigned int>::max() );
    unsigned int i = 0;
    for ( typename std::list<T>::const_iterator it = Arg.begin();
          it != Arg.end(); ++it, ++i ) {
        if ( (*it) > (res.first) ) {
            res.first = (*it);
            res.second = i;
        }
    }
    return ( res );
}
// ...
std::pair<double, unsigned int> maxAndPos = findMaximumAndItsPosition ( myList );
```

~~ [STLUtilities\\_Pair.cpp](#)

## 5. Algorithms and Utilities

### Min, Max, Swap

```
#include<cstdlib>
#include<iostream>

int main ( const int, const char** const ) {
    int a = 23, b = 42;
    std::cout << "Maximum is " << std::max ( a, b ) << std::endl;
    std::cout << "Minimum is " << std::min ( a, b ) << std::endl;

    std::swap ( a, b );
    std::cout << "Now a=" << a << ", b=" << b << std::endl;

    return ( EXIT_SUCCESS );
}
```

→ STLUtilities\_MinMaxSwap.cpp

## 5. Algorithms and Utilities

### Maximum with Comparator

```
int weightedTimeSinceMeal ( const int Hour ) {
    static const int hPD = 24; // hours per day

    const int hour = Hour % hPD;
    if ( hour < 8 ) { return ( ( ( hPD + hour - 20 ) % hPD ) / 2 ); }
    else if ( hour < 12 ) { return ( 2 * ( hour - 8 ) ); }
    else if ( hour < 20 ) { return ( ( hour - 12 ) ); }
    else { return ( ( ( hour - 20 ) % hPD ) / 2 ); }

}

bool hungerCompare ( const int HourA, const int HourB ) {
    return ( weightedTimeSinceMeal ( HourA ) < weightedTimeSinceMeal ( HourB ) );
}
// ...

const int timeA = 11, timeB = 14;

std::cout << "Comparing " << timeA << " and " << timeB
        << ", more hungry at " << std::max ( 11, 14, hungerCompare ) << std::endl;
```

↔ STUtilities\_Compare.cpp

## 5. Algorithms and Utilities

### Sorting 1

```
#include<vector>
#include<set>
#include<algorithm>

const size_t mySize = 8;
const float myArray[mySize] = { 0.2, 0.8, 1.9, 1.7, 0.3, 1.1, 1.5, 0.4 };

std::vector<float> myVector ( myArray, myArray+mySize );
std::sort ( myVector.begin(), myVector.end() );

std::sort ( myVector.begin(), myVector.end(), std::greater<float>() );

std::set<float, std::greater<float> > mySet ( myArray, myArray+mySize );
```

## 5. Algorithms and Utilities

### Sorting 2

```
#include<vector>
#include<algorithm>

template<typename FloatDataType>
struct lessAsInt {
    bool operator() ( const FloatDataType A, const FloatDataType B ) const {
        return ( ( static_cast<int> ( A ) < static_cast<int> ( B ) ) );
    }
};

std::vector<float> myVectorB ( myArray, myArray+mySize );
std::sort ( myVectorB.begin(), myVectorB.end(), lessAsInt<float>() );

std::sort ( myArray, myArray+mySize ); // sort C array
```

↔ STLalgorithms\_Sorting.cpp

## 5. Algorithms and Utilities

### Generators 1

```
int consecutiveNumber() {
    static int counter = 0;
    return ( counter++ );
}

class UniqueNumberGenerator {
public:
    UniqueNumberGenerator() : _num ( 0 ) {
    }

    int operator()() {
        _num += 3;
        return ( _num );
    }

private:
    int _num;
};
```

## 5. Algorithms and Utilities

### Generators 2, Transform, Accumulate

```
#include<vector>
#include<algorithm>
#include<functional>
// ...
const size_t mySize = 10;
std::vector<int> myVectorA ( mySize );
std::generate ( myVectorA.begin(), myVectorA.end(), consecutiveNumber );

std::vector<int> myVectorB ( mySize );
std::generate ( myVectorB.begin(), myVectorB.end(), UniqueNumberGenerator() );

std::vector<int> myVectorC ( mySize );
std::transform ( myVectorA.begin(), myVectorA.end(),
                 myVectorB.begin(), myVectorC.rbegin(), std::plus<int>() );
const int
    init = 50,
    result = std::accumulate ( myVectorA.begin(), myVectorA.end(),
                               init, std::minus<int>() );
std::cout << "result = " << result << std::endl;
```

→ STLalgorithms\_Generate.cpp

## 5. Algorithms and Utilities

### Find and Iterator Arithmetics

```
#include<vector>
#include<algorithm>

typedef unsigned short ushort;
const size_t mySize = 10;

// std::find works with C arrays as well as STL data structures

const ushort myArray[mySize] = { 0, 2, 4, 6, 8, 10, 12, 14, 12, 12 };
const ushort* p = std::find ( myArray, myArray+mySize, 12 );
if ( ( p - myArray ) < mySize ) {
    std::cout << "Found" << *p << " at position" << p - myArray << std::endl;
} // else, p == myArray+mySize indicating not found

std::vector<ushort> myVector ( myArray, myArray+mySize );
std::vector<ushort>::iterator
pos = std::find ( myVector.begin(), myVector.end(), 14 );
if ( pos != myVector.end() ) {
    std::cout << "Found" << *pos << " at position"
        << pos - myVector.begin() << std::endl; // iterator difference
} // else not found
```

## 5. Algorithms and Utilities

### Count, Shuffle and Minmax\_Element

```
#include<ctime>
#include<random>
// ...

const int numCount = std::count ( myArray, myArray+mySize, 12 );
std::cout << "12 is contained" << numCount << " times." << std::endl;

unsigned int mySeed = static_cast<int> ( std::time(0) );
std::shuffle ( myVector.begin(), myVector.end(), std::mt19937 ( mySeed ) );

std::pair< std::vector<ushort>::iterator,
           std::vector<ushort>::iterator >
minMax = std::minmax_element ( myVector.begin(), myVector.end() );

std::cout << "Minimum of" << * ( minMax.first )
     << " at" << minMax.first - myVector.begin() << ","
     << "maximum of" << * ( minMax.second )
     << " at" << minMax.second - myVector.begin() << std::endl << std::endl;
```

similarly: `std::count_if`, `std::min_element`, `std::max_element`

## 5. Algorithms and Utilities

### Partitioning and Binary Search

```
bool isDivisibleByFour ( const ushort &Arg ) {
    return ( ( Arg % 4 ) == 0 );
}

bool veryExpensiveComparison ( const ushort &A, const ushort &B ) {
    std::cout << "VERY_EXPENSIVE_COMPARISON" << std::endl;
    return ( ( A < B ) );
}

// ...

std::vector<ushort> myVector2 ( myVector );
std::partition ( myVector2.begin(), myVector2.end(), isDivisibleByFour );
std::stable_partition ( myVector.begin(), myVector.end(), isDivisibleByFour );
bool found = std::binary_search ( myVector.begin(), myVector.end(),
                                 14, veryExpensiveComparison );
```

↔ STLAlgorithms\_Misc.cpp

## 6. Summary

1. Introduction

2. Concepts

3. Containers

4. Iterators

5. Algorithms and Utilities

**Contact:** Ole Schwen <ole.schwen@mevis.fraunhofer.de>

## 6. Summary

»Pinguine gibt es diesmal keine. Versprochen!«

Last time the organizers promised this, it didn't work ...

## 6. Summary

»Pinguine gibt es diesmal keine. Versprochen!«

Last time the organizers promised this, it didn't work ...

